

PK-75-2-122 CCTV COAXIAL CABLE

KT2603 (BC SPE AL/Pet 45% TCCA | TC 3.3 PVC | PE)

Construction Parameters:

Inner Conductor	0.37mm Bare Copper
Dielectric	2.20±0.05mm Solid Polyethylene
First Shield	AL/Pet
Second Shield	Braiding
Strands	0.005"/0.12mm CCA BC
% Coverage	45-50 nom
Jacket	3.30±0.30mm PVC PE
Application	For Use in Intermediate CCTV Run Lengths
Limited Length	



Electrical Characteristics:

Capacitance	68±1 pF/m
Impedance	75±5 Ω
Resistance	168.2 Ohms/KM
Return loss	
Velocity of Propagation	0.66
Shielding Effectiveness(>dB)	
Max Operating Voltage(KVMS)	
Operating Temp Range (PVC)	-20 °C -40°C -60°C to 60°C
RoHS	YES

Attenuation(20 °C):

Frequency (MHZ)	Max Attenuation (dB/100m)
10	6.40
50	12.70
200	24.00
470	37.60
862	52.10
1000	56.70
1350	65.60
1750	76.80
2150	85.80
2400	97.90
3000	107.00

Order Informations:

Marking	KINGTONE KT2603 PK-75-2-122 COAXIAL CABLE XXXFT/M
Package	100M/REEL, 500M/Wooden Spool,Pallet
Delivery time	Normally 20-25 days after received the deposit.
More informations	please contact with us.

Online Service:

Skype	kingtone3
ICQ	246632889