

RG59 95% Bonded PVC-WOP

KT2115

KINGTONE
ELECTRONICS

Construction Parameters:

Inner Conductor	0.032"/0.81mm/20AWG Copper Clad Steel
Dielectric	0.144"/3.66mm Foamed PE(Gas Expanded Polyethylene)
Shield 1	0.151"/3.84mm Bonded.Aluminum
Shield 2	Aluminum braid wire 95% coverage
Application	For Use in Longer CATV Run Lengths

Electrical Characteristics:

	The Max.at 20°C shall be <87 Ω/km
Inner Conductor Resistance	26.5 Ω/1000ft
Capacitance	52 ±3 pF/m 15.8 ±1 pF/ft
Impedance	75 ± 3 Ω
Return loss	between 5 and 1000MHz: > 22dB
Velocity of Propagation	0.85
Sparker Test (VAC)	4



Attenuation(20°C):

Frequency (MHZ)	Max Attenuation(dB/100ft)	Max Attenuation (dB/100m)
5	0.86	2.82
55	2.05	6.73
83	2.45	8.04
187	3.60	11.81
211	3.80	12.47
250	4.10	13.45
300	4.45	14.60
350	4.80	15.75
400	5.10	16.73
450	5.40	17.72
500	5.70	18.70
550	5.95	19.52
600	6.20	20.34
750	6.97	22.87
865	7.52	24.67
1000	8.12	26.64

Mechanical and Environmental Properties

Cable bend radius	10 times the cable diameter
Operating Temp Range (PVC)	-20 °C to 60°C
Cable dimensions Suggestion	0.242"±0.006"/6.15±0.15 mm PVC

Order Informations:

Package	5000m/Wooden Spool/Pallet
Wooden Spool Dimensions	57×57×55 CM
Delivery time	Normally 25 days after received the deposit.

Online Service:

Skype	kingtone3
ICQ	246632889