

RG59 ST CCTV POWER CABLE

KT0723

VR-90C

Construction Parameters:

Inner Conductor	0.64mm/22AWG Bare Copper
Dielectric	3.7±0.05mm Solid PE
Shield	Nom. 4.15mm
Strand	0.12mm/34AWG Copper Clad Aluminum
% Coverage	95 nom.
Jacket	6.00±0.1mm PVC (Color by your choice)
Power Wire Conductor	34×0.20mm Copper Clad Aluminum
Power wire Diameter of insulation	2.1mm PVC
Power Wire Color Code	Red,Black
Jacket	5.3±0.1mm PVC
* 1 Pair of wire twisted	



Electrical Characteristics:

Capacitance	67±2 pF/m
Impedance	75±3 Ω
Inner Conductor Resistance	54 Ohms/KM at 20℃
Return loss	between 5 and 1000MHz: > 22.5dB
Velocity of Propagation	0.66
Sparker Test (VAC)	3
Operating Temp Range (PVC)	-20 °C to 65℃
RoHS	YES

Attenuation(20℃):

Frequency (MHZ)	Max Attenuation (dB/100m)
5	2.68
55	9.56
187	18.24
211	19.51
350	25.64
450	29.39
550	32.76
750	38.92
865	42.30
100	46.17

Order Informations:

Marking	KINGTONE KT0723 RG59ST 95%CCA +2C-1.00MM ² CCA CLASS 5 CE RoHS 70C XXXM MMDDYYYY
Package	100M/Plastic Spool,300M/500M/Wooden Spool,Carton
Delivery time	Normally 20-25 days after received the deposit.
More informations	please contact with us.

Online Service:

Skype	kingtone3
ICQ	246632889