

RG59 B/U BCCCA CCTV CABLE

KT0707

Construction Parameters:

Inner Conductor	0.58mm/23AWG Bare Copper
Dielectric	3.66±0.05mm Solid PE
Shield	Nom. 4.10mm
Strand	0.12mm Copper Clad Aluminum
% Coverage	95 nom.
Jacket	6.00±0.1mm PVC (Color by your choice)
Application	For Use in Intermediate CCTV Run Lengths
Limited Length	Typical run length up to 250M



Electrical Characteristics:

Capacitance	67±2 pF/m
Impedance	75±3 Ω
Inner Conductor Resistance	65.26 Ohms/KM at 20°C
Return loss	between 5 and 1000MHz: > 22dB
Velocity of Propagation	0.66
Sparker Test (VAC)	3
Operating Temp Range (PVC)	-20 °C to 65°C
RoHS	YES

Attenuation(20°C):

Frequency (MHZ)	Max Attenuation (dB/100m)
5	2.70
50	9.00
100	12.87
200	18.54
550	31.98
750	37.81
865	41.15
1000	44.65

Order Informations:

Marking	KINGTONE KT0707 RG59 B/U BC SPE 95% CCA ***M
Package	100m/Spool,300m/Wooden Spool,Pallet
Delivery time	Normally 20-25 days after received the deposit.
More informations	please contact with us.

Online Service:

Skype	kingtone3
ICQ	246632889