
Application

Internal wiring of electronic equipment, computers, business machines and appliances

Description

- Stranded Tinned Copper, Color Coded
- Irradiated PVC , .017" Nominal Wall
- Temperature Range: -55°C to +105°C
- Voltage Rating: 1000 Volts



Specification

AWG SIZE	Conductor Stranded	NOM O.D. (Inches)	NOM O.D. (mm)	UL STYLE
26	7/34	0.051	1.2954	1430
26	19/36	0.053	1.3462	1430
24	7/32	0.058	1.4732	1430
24	19/36	0.058	1.4732	1430
22	7/30	0.064	1.6256	1430
22	19/34	0.064	1.6256	1430
20	7/28	0.072	1.8288	1430
20	19/32	0.072	1.8288	1430
18	7/26	0.082	2.0828	1430
18	19/30	0.082	2.0828	1430
16	19/28	0.091	2.3114	1430
14	19/27	0.016	0.4064	3317
12	19/25	0.016	0.4064	3317
14	19/27	0.105	2.667	3317
12	19/25	0.124	3.1496	3317
10	37/.0167	0.149	3.7846	3317

Order Informations:

Marking	KINGTONE KT1204 UL1430 HOOK UP WIRE XXX M/FT
Inner Package	500FT/Pull Box, 1000FT/Wooden Spool, Pallet
Delivery time	Normally 15 days after received the deposit.

Online Service:

Skype	kingtone3
ICQ	246632889
