

0.22mm² Shielded Alarm Cable

KT1302

Applications

Wiring Burglar & Security alarms, public address systems, intercoms, telephone stations, speakers, instrumentation, control and other low voltage circuits that are power limited.

Construction

Conductor	7x0.0078"/7 x 0.20mm TC/BC/CCA/TCCA
Shielded	AL/PE FOIL
Insulation	0.037"/0.95mm PVC
Drain Wire	TC/BC/CCA/TCCA
Rip Cord	Cotton Wire
Outer jacket	PVC(RoHs) flame retardant



Structure of single shielded 0.22mm² soft alarm cable

Serial No.	Section	Specification	Qverall Diameter(mm)
A-01	2*0.22mm ²	2*7/0.20	3.1
A-02	4*0.22mm ²	4*7/0.20	3.6
A-03	6*0.22mm ²	6*7/0.20	4.2
A-04	8*0.22mm ²	8*7/0.20	4.6
A-05	10*0.22mm ²	10*7/0.20	5.3
A-06	12*0.22mm ²	12*7/0.20	5.5
A-07	14*0.22mm ²	14*7/0.20	5.9
A-08	20*0.22mm ²	20*7/0.20	6.9
A-09	30*0.22mm ²	30*7/0.20	8.5
A-10	40*0.22mm ²	40*7/0.20	10.1
A-11	2*0.5+2*0.22mm ²	2*16/0.20+2*7/0.20	4
A-12	2*0.5+4*0.22mm ²	2*16/0.20+4*7/0.20	4.6
A-13	2*0.5+6*0.22mm ²	2*16/0.20+6*7/0.20	5
A-14	2*0.5+8*0.22mm ²	2*16/0.20+8*7/0.20	5.8
A-15	2*0.5+10*0.22mm ²	2*16/0.20+10*7/0.20	6.1
A-16	2*0.5+12*0.22mm ²	2*16/0.20+12*7/0.20	6.4
A-17	2*0.75+2*0.22mm ²	2*24/0.20+2*7/0.20	4.3
A-18	2*0.75+4*0.22mm ²	2*24/0.20+4*7/0.20	5
A-19	2*0.75+6*0.22mm ²	2*24/0.20+6*7/0.20	5.4
A-20	2*0.75+8*0.22mm ²	2*24/0.20+8*7/0.20	6.3

Order Informations:

Marking	KINGTONE KT1302 0.22mm ² Shielded Alarm Cable XXX M/FT (or Per customer's request)
Package	100m/Roll, 100m/Spool, 305m/Spool, Pallet (or Per customer's request)
Delivery time	Normally 15 days after received the deposit.

Online Service:

Skype	kingtone3
ICQ	246632889