

1-1/4" Leaky KT0300

Construction Parameters:

Inner Conductor	0.516"/13.1mm Smooth Copper Tube
Dielectric	1.312"/33.3mm Foamed PE
Outer Conductor	Nom.1.418"/36.0mm Corrugated Copper Tube and Slot
Jacket	1.520"/38.6mm Black PE/Low Smoke Halogen-free Fire-retardant PE

Electrical Characteristics:

Capacitance	76 pF/m 23.17 pF/ft
Impedance	50 Ω
Velocity of Propagation	0.88
Insulation Resistance (M. Ω .KM)	>5000
Insulation Voltage(KV)	10
Jacket Sparkt (KV)	10



Mechanical and Environmental:

Min.Single Bending Radius (mm)	150
Mobile Apply (mm)	700
No. of Bends	50
Tensile Strength(kg)	290
Operating Temp.(°C)	-55 to +85 °C

Attenuation(20 °C):

Frequency (MHZ)	Attenuation (dB/100m)	Coupling Loss (50%/90%,dB)
75	0.8	61/71
150	1.1	64/74
450	2.5	75/85
800	3.3	76/86
900	3.5	76/86
1800	5.0	77/87
2200	5.9	77/87
2400	6.5	78/88

Order Informations:

Marking	KINGTONE KT0300 1-1/4" Leaky COAXIAL CABLE XXX M/FT
Package	100m/Roll, 100m/Spool,305m/Spool,Pallet
Delivery time	Normally 15 days after received the deposit.
More informations	please contact with us.

Online Service:

Skype	kingtone3
ICQ	246632889
