


670-086/75 SXE Semi Flexible Cable KT0804

Construction Parameters:

Inner Conductor	0.011"/0.29mm Silver Plated Copper Clad Steel
Dielectric	0.066"/1.68mm PTFE
Outer Conductor	Nom.0.083"/2.1mm Tin Soaked Copper Braid
Jacket	0.098"/2.50mm FEP

Electrical Characteristics:

Capacitance	63.5 pF/m	19.4 pF/ft
Impedance	75 Ω	
Velocity of Propagation	0.695	
Operating Frequency (GHz)	61	
Time Delay(ns/m)	4.7	
Max. Operating Voltage (kVrms)	1.5	



Mechanical and Environmental:

Min. Bending Radius (mm)	6
Min.Repeated Bending Radius (mm)	20
Operating Temp.(°C)	-55 to +125 °C

Attenuation(20 °C):

Frequency (GHZ)	Attenuation (dB/100m)	Power(Watts CW)
0.5	48.00	173.30
1.0	68.00	121.40
5.0	160.00	52.20
10.0	234.00	35.90
20.0	347.00	24.40

Order Informations:

Marking	KINGTONE KT0804 670-086/75 SXE XXX M/FT (or Per customer's request)
Package	100m/Roll, 100m/Spool,305m/1000ft/Spool/Pallet (or Per customer's request)
Delivery time	Normally 15 days after received the deposit.
More informations	please contact with us.

Online Service:

Skype	kingtone3
ICQ	246632889
