TXL Automotive Wire

KT1508

Features

Type TXL Cable, Primary Wire may be used in automotive
Recommended temperature range for TXL Wire is -40°C to
TXL Wire voltage rating is 50 Volts
TXL Wire is available in solid colors and stripes with optional
Available in drumpacks on many sizes

Types

Part Number	Conductor Stranding	Nom. Insul. Thick. (in)	Nom. Insul. Thick. (mm)	Nom. O.D. (in)	Nom. O.D. (mm)	Approx LBS/MFT
TXL-22	7/30	0.016	0.41	0.062	1.57	3
TXL-20	7/28	0.016	0.41	0.07	1.78	5
TXL-18	16/30	0.016	0.41	0.079	2.01	6.9
TXL-16	19/29	0.016	0.41	0.089	2.26	9.4
TXL-14	19/27	0.016	0.41	0.103	2.62	14.1
TXL-12	19/25	0.018	0.46	0.126	3.20	22.2
TXL-10	19/23	0.02	0.51	0.155	3.94	35
TXL-8	19/.285	0.026	0.66	0.142	3.61	24

Order Informations:

Marking	KINGTONE KT1508 TXL AUTOMOTIVE WIRE XXX M/FT
Package	500FT/Pull Box, 1000FT/Wooden Spool,Pallet
Delivery time	Normally 15 days after received the deposit.

Online Service:

Skype	kingtone3
ICQ	246632889