

0.2mm² Shielded Alarm Cable

KT1300

Applications

Wiring Burglar & Security alarms, public address systems,intercoms, telephone stations, speakers,instrumentation,control and other low voltage circuits that are power limited.

Construction

Conductor	0.020"/0.50mm TC/BC/CCA/TCCA
Shielded	AL/PE FOIL
Insulation	0.037"/0.95mm PVC
Drain Wire	TC/BC/CCA/TCCA
Rip Cord	Cotton Wire
Outer jacket	PVC(RoHs) flame retardant



Structure of single shielded 0.2mm² soft alarm cable

Serial No.	Section	Specification	Qverall Diameter(mm)
C-01	2*0.2mm ²	2*1/0.50	3.1
C-02	4*0.2mm ²	4*1/0.50	3.6
C-03	6*0.2mm ²	6*1/0.50	4.3
C-04	8*0.2mm ²	8*1/0.50	4.6
C-05	10*0.2mm ²	10*1/0.50	5.4
C-06	12*0.2mm ²	12*1/0.50	5.6
C-07	16*0.2mm ²	16*1/0.50	6.1
C-08	24*0.2mm ²	24*1/0.50	7.4

Order Informations:

Marking	KINGTONE KT1300 0.2mm ² Shielded Alarm Cable XXX M/FT (or Per customer's request)
Package	100m/Roll, 100m/Spool,305m/Spool,Pallet (or Per customer's request)
Delivery time	Normally 15 days after received the deposit.

Online Service:

Skype	kingtone3
ICQ	246632889