

UL 1061 HOOK UP WIRE

KT1202



Application

UL 1061 Lead Wire may be used for the internal wiring of electronic equipment

Description

- Stranded Tinned Copper, Color Coded
- Semi-Rigid Polyvinylchloride Insulation
- Temperature Range: -10°C to +80°C
- Voltage Rating: 300 Volts



Specification

AWG SIZE	Conductor	Stranded	NOM O.D. (Inches)	NOM O.D. (mm)	UL STYLE
30	Solid		0.03	0.76	1061
28	Solid		0.033	0.84	1061
28	7/36		0.035	0.89	1061
26	Solid		0.038	0.97	1061
26	7/34		0.039	0.99	1061
24	Solid		0.042	1.07	1061
24	7/32		0.045	1.14	1061
22	Solid		0.047	1.19	1061
22	7/30		0.051	1.30	1061
20	Solid		0.053	1.35	1061
20	7/28		0.057	1.45	1061
20	10/30		0.056	1.42	1061
18	Solid		0.061	1.55	1061
18	16/30		0.067	1.70	1061
18	19/30		0.066	1.68	1061
16	Solid		0.072	1.83	1061
16	19/28		0.078	1.98	1061
16	26/30		0.081	2.06	1061

Order Informations:

Marking	KINGTONE KT1202 UL1061 HOOK UP WIRE XXX M/FT
Inner Package	500FT/Pull Box, 1000FT/Wooden Spool, Pallet
Delivery time	Normally 15 days after received the deposit.

Online Service:

Skype	kingtone3
ICQ	246632889
